SPECIFICATIONS

2017 BRUTE FORCE® 750 4x4i EPS CAMO



POWER

Engine Displacement Bore x Stroke Compression ratio Fuel System Ignition Transmission Final Drive

CAPABILITY

Front Suspension / Wheel Travel Rear Suspension / Wheel Travel Front Tire Rear Tire Front Brakes Rear Brakes Ground Clearance Starting System Fuel Capacity Turning Radius Towing Capacity Total Rack Capacity Rack Capacity, Front/Rear Lighting 85.0 x 66.0mm 9.3:1 DFI® with two 36mm throttle bodies Digital DC-CDI 2-Speed automatic, reverse Selectable 4WD with variable front differential control, shaft Double wishbone/6.7 in

4-stroke, V-twin, SOHC, liquid-cooled

749cc

Full independent, dual A-arm/7.5 in AT 25 x 8-12 AT 25 x 10-12 Dual hydraulic 200mm discs with 2-piston calipers Sealed, oil-bathed, multi-disc 9.4 in Electric 5.0 gal 10.5 ft 1250 lb 242.0 lb 88.0 lb/176.0 lb 35W headlights, 5W taillight, 21W stoplight

DETAILS

| Frame Type | Double-cradle, high-tensile tubular steel |
|--------------------------------------|---|
| Track Front/Rear | 36.4/35.0 in |
| Overall Length | 86.4 in |
| Overall Width | 46.5 in |
| Overall Height | 48.0 in |
| Seat Height | 35.8 in |
| Curb Weight | 699.0 lb** |
| Wheelbase | 50.6 in |
| Instruments | Speedometer, odometer, dual trip meters, fuel gauge, engine temp, clock, hour meter and 2WD/4WD icon, plus indicators |
| | for EPS, neutral, belt, and oil pressure |
| Color Choices | Realtree Xtra® Green Camo |
| Warranty | 12 Month Limited Warranty |
| Kawasaki Protection Plus™ (optional) | 12, 24, 36, or 48 months |
| | |

**Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).