

Mule Pro MX specs

Engine

Engine type

Liquid-cooled, 4-stroke Single

Displacement

695 cm³

Bore x stroke

102 x 85 mm

Compression ratio

10.3:1

Fuel system

Fuel injection: Ø44 mm x 1 throttle body

Ignition

Magneto & transistor

Starting System

Electric

Lubrication

Forced lubrication, wet sump

Performance & Transmission

Maximum power

32.8 kW {45 PS} / 6,000 rpm

Maximum torque

57.6 N•m {5.8 kgf•m} / 5,000 rpm

Transmission

CVT, 2 speed auto, reverse

Final drive

Shaft 2WD/4WD

Primary Reduction Ratio

3.653 ~ 0.794 (belt converter)

Brakes & Suspension

Brakes, front
Dual 186 mm discs

Brakes, rear
Dual 174 mm discs

Suspension, front
Double Wishbone

Suspension, rear
Double Wishbone

Frame & Dimensions

Frame type
Ladder type, tubular steel

Wheel travel front
218 mm

Wheel travel rear
232 mm

Tyre, front
25 x 8.00 R12

Tyre, rear
25 x 10.00 R12

Steering angle, left / right
43o (IN) / 38o (OUT),

L x W x H
2,795 x 1,525 x 1,890 mm

Wheelbase
2,005 mm

Ground clearance
270 mm

Fuel capacity
36 litres

Seat height
850 mm

Curb mass
719 kg